

1. THIS CONCEPTUAL DETAIL IS A GUIDE FOR INSTALLATION OF NICHIIA PRODUCTS. ARCHITECTS/ENGINEERS/CONTRACTORS ARE RESPONSIBLE FOR SUCCESSFUL APPLICATION WHICH DEPENDS UPON SUBSTRATE DESIGN AND CONSTRUCTION BUILT IN ACCORDANCE WITH BEST PRACTICES AND LOCAL BUILDING CODES.
2. METAL FURRING CHANNEL MUST BE C-STUD, "Z", OR HAT CHANNEL (SHOWN HERE) AND MUST BE A MINIMUM OF 18 GA.
3. COMPLY WITH LOCAL BUILDING CODE REQUIREMENTS FOR WEATHER/WATER RESISTANT BARRIERS.
4. NICHIIA PANEL REPRESENTED HERE IS 5/8" PRODUCT, ADJUST ACCORDINGLY FOR OTHER PRODUCT THICKNESSES.
5. REFER TO AWP HORIZONTAL INSTALL GUIDE FOR EXPANSION JOINT REQUIREMENTS ASSOCIATED WITH AWP-1818 AND METAL TRIM OUTSIDE CORNERS.
6. MITER CUT PANEL EDGES TO FIT FULLY WITHIN CORNER KEY TRIM IN LIGHT CONTACT.
7. DETAIL DATE: 06-21-2019



SCALE: $1\frac{1}{2}" = 1'-0"$